

Quick Reference Guide

Model	EPC-945	EPC-AT270
CPU	Supports 65nm Intel® µFC-PGA 478/µFC-BGA 479 Core™ Duo/Core™ Duo/Celeron® M CPU	Onboard Intel® Atom™ N270 1.6GHz CPU
BIOS	Award 4 MBit Flash BIOS	Award 8 MBit Flash BIOS
System Chipset	Intel® 945GME / ICH7-M	Intel® 945GSE/ICH7-M
I/O Chipset	Winbond W83627HF-AW	ITE 8712F
System Memory	One 200-pin SODIMM supports up to 2 GB DDR2 400/533/667 SDRAM	One 200-pin SODIMM supports up to 2 GB DDR2 400/533 SDRAM
SSD	One CompactFlash Type I/II socket	
Watchdog Timer	Reset: 1 sec.~255 min. and 1 sec. or 1 min./step	
Display	Intel® 945GME Integrated GMA 950 graphic	Intel® 945GSE Integrated
Audio	Realtek ALC883 supports 7.1-CH Audio	Realtek ALC655 supports 5.1-CH Audio
Ethernet	Dual Realtek RTL8111C PCI-E Gigabit Ethernet, supports wake on LAN (RTL8111B for Rev. A1)	Dual Marvell 88E8053 Gigabit Ethernet, supports Wake on LAN
System Indicators	2 LED indicators show the power and HDD	
Drive Bay	Mounting kit for one 2.5" HDD(hidden)	
Expansion Interface	-----	1 x Mini PCIe
Serial Port	1 x RS-232	1x RS-232, 1xRS232/422/485
Ethernet Port	2 x RJ-45	
WiFi	Optional (USB Module)	
DVI	-----	1 x DVI (Optional)
VGA / LCD Port	1 x DB-15	
Audio Port	Mic-in, Line-in, Line-out	
USB Port	3 x USB 2.0	5 x USB 2.0
Mouse & KB	1 x PS/2 mini DIN	1 x PS/2 mini DIN (Optional)
Power Input	100 ~ 240 Vac / 50 ~ 60 Hz	
Power Output	+12 V	
Operating Temperature	0~40°C (32~104°F)	
Storage Temperature	-20 to +75°C (-4~167°F)	
Relative Humidity	5 to 90% @ 40°C (104°F), relative humidity, non-condensing	
Dimension (W x D x H)	7.0" x 5.6" x 2.0" (178 x 142 x 50 mm)	7.0" x 4.4" x 2.0" (178 x 112 x 50 mm)
Weight	2.7 lbs (1.2 Kgs)	
Mounting	VESA Compliance	